

I. Introduction: roadmap

I.1 what *is* the Internet?

I.2 network edge

- end systems, access networks, links

I.3 network core

- packet switching, circuit switching, network structure

I.4 delay, loss, throughput in networks

I.5 protocol layers, service models

I.6 networks under attack: security

I.7 history



Self study



Quiz: Circuit Switching

Consider a circuit-switched network with $N=100$ users where each user is independently active with probability $p=0.2$ and when active, sends data at a rate of $R=1\text{Mbps}$. How much capacity must the network be provisioned with to guarantee service to all users?

- A. 100 Mbps
- B. 20 Mbps
- C. 200 Mbps
- D. 50 Mbps
- E. 500 Mbps

Answer: A
(probability of activity is irrelevant)
 $100 \times 1 \text{ Mbps} = 100 \text{ Mbps}$

Open a browser and type: www.pollev.com/salil



Quiz: Statistical Multiplexing

Consider a packet-switched network with $N=100$ users where each user is independently active with probability $p=0.2$ and when active, sends data at a rate of $R=1$ Mbps. What is the expected aggregate traffic sent by all the users?

- A. 100 Mbps
- B. 20 Mbps
- C. 200 Mbps
- D. 50 Mbps
- E. 500 Mbps

Answer: B

$$100 \times 0.2 \times 1 \text{ Mbps} = 20 \text{ Mbps}$$

Open a browser and type: www.pollev.com/salil

Quiz: Delays




Consider a network connecting hosts A and B through two routers R1 and R2 like this: A-----R1-----R2-----B. Does whether a packet sent by A destined to B experiences queuing at R1 depend on the length of the link R1-R2?

- A. Yes, it does
- B. No, it doesn't

Answer: B

Queuing happens because R1 cannot transmit packets on the R1-R2 link fast enough, i.e., the transmission rate of the R1-R2 link is low. The length of the R1-R2 link does not typically impact this.



Open a browser and type: www.pollev.com/salil

Three (networking) design steps

- ❖ Break down the problem into tasks
- ❖ Organize these tasks
- ❖ Decide who does what

Tasks in Networking

- ❖ What does it take to send packets across?
- ❖ Prepare data (Application)
- ❖ Ensure that packets get to the dst process (Transport)
- ❖ Deliver packets across global network (Network)
- ❖ Delivery packets within local network to next hop (Datalink)
- ❖ Bits / Packets on wire (Physical)

This is decomposition...

Now, how do we organize these tasks?

Let us have an example

Inspiration...

- ❖ CEO A writes letter to CEO B
 - Folds letter and gives it to Executive Assistant (EA)

Dear John,

Your days are numbered.

--Grace

» EA:


» Puts letter in envelope with CEO B's full name

» Takes to FedEx

- ❖ FedEx Office
 - Puts letter in larger envelope
 - Puts name and street address on FedEx envelope
 - Puts package on FedEx delivery truck
- ❖ FedEx delivers to other company

The Path of the Letter


“Peers” on each side understand the same things
No one else needs to (abstraction)
Lowest level has most packaging



The Path Through FedEx


Higher “Stack”
at Ends

Partial “Stack”
During Transit




Deepest Packaging (Envelope+FE+Crate)
at the Lowest Level of Transport

In the context of the Internet




Internet protocol stack

- ❖ **application:** supporting network applications
 - FTP, SMTP, HTTP, Skype, ..
- ❖ **transport:** process-process data transfer
 - TCP, UDP
- ❖ **network:** routing of datagrams from source to destination
 - IP, routing protocols
- ❖ **link:** data transfer between neighboring network elements
 - Ethernet, 802.111 (WiFi), PPP
- ❖ **physical:** bits “on the wire”




Three Observations

- ❖ Each layer:
 - Depends on layer below
 - Supports layer above
 - Independent of others
- ❖ Multiple versions in layer
 - Interfaces differ somewhat
 - Components pick which lower-level protocol to use
- ❖ But only one IP layer
 - Unifying protocol




An Example: No Layering



- ❖ No layering: each new application has to be re-implemented for every network technology !

An Example: Benefit of Layering

- ❖ Introducing an intermediate layer provides a **common** abstraction for various network technologies



Is Layering Harmful?

- ❖ Layer N may duplicate lower-level functionality
 - E.g., error recovery to retransmit lost data
- ❖ Information hiding may hurt performance
 - E.g., packet loss due to corruption vs. congestion
- ❖ Headers start to get large
 - E.g., typically, TCP + IP + Ethernet headers add up to 54 bytes
- ❖ Layer violations when the gains too great to resist
 - E.g., Network Address Translation (NAT – to be covered in Network Layer)
- ❖ Layer violations when network doesn't trust ends
 - E.g., Firewalls (Security)

Distributing Layers Across Network

- ❖ Layers are simple if only on a single machine
 - Just stack of modules interacting with those above/below
- ❖ But we need to implement layers across machines
 - Hosts
 - Routers
 - Switches
- ❖ What gets implemented where?


What Gets Implemented on Host?

- ❖ Hosts have applications that generate data/messages that are eventually put out on wire
- ❖ At receiver host bits arrive on wire, must make it up to application
- ❖ Therefore, all layers must exist at host!

What Gets Implemented on Router?


- ❖ Bits arrive on wire
 - Physical layer necessary
- ❖ Packets must be delivered to next-hop
 - datalink layer necessary
- ❖ Routers participate in global delivery
 - Network layer necessary
- ❖ Routers don't support reliable delivery
 - Transport layer (and above) **not** supported

Internet Layered Architecture




Logical Communication

- ❖ Layers interacts with peer's corresponding layer




Physical Communication



- ❖ Communication goes down to physical network
- ❖ Then from network peer to peer
- ❖ Then up to relevant layer



Encapsulation








source



switch

destination



router

Quiz: Layering



What are two benefits of using a layered network model ? (Choose two)

- A. It makes it easy to introduce new protocols
- B. It speeds up packet delivery
- C. It allows us to have many different packet headers
- D. It prevents technology in one layer from affecting other layers
- E. It creates many acronyms
- F. It reminds me of cake

Answer: A+D

C and E are true statements, but side-effects not benefits, yum I also love cake

Open a browser and type: www.pollev.com/salil

I. Introduction: roadmap

I.1 what *is* the Internet?

I.2 network edge

- end systems, access networks, links


I.3 network core

- packet switching, circuit switching, network structure

I.4 delay, loss, throughput in networks

I.5 protocol layers, service models

I.6 networks under attack: security



Self study

I.7 history